

Technical data	A-17 PLUS	A-22 PLUS	A-28 PLUS
Power supply voltage		220/240V 50Hz 220/230V 60Hz	
Rated power		2300 W	
External dimensions W x H x D		480 x 500 x 600 mm	
Chamber dimensions Diam. x Depth	250 x 350 mm	250 x 450 mm	280 x 450 mm
Total weight	51 kg	52 kg	53 kg
Tank capacity		4.5 litres	
Autonomy (with max. water level)	From 7 to 11 cycles	From 6 to 10 cycles	From 5 to 9 cycles

CYCLE	Cycle type	Sterilization time (min.)	Cycle times including sterilization times, net of drying times (min.)			Drying*
			A-17 PLUS	A-22 PLUS	A-28 PLUS	
134 °C UNIVERSAL	B	4	29	31	39	13-17
121 °C UNIVERSAL	B	20	45	48	52	13-17
134 °C UNWRAPPED HOLLOW INSTRUMENTS	S	4	31	34	38	4-6
134 °C WRAPPED SOLID INSTRUMENTS	S	4	20	24	28	13-17
134 °C PRION	B	18	43	45	53	13-17
xxx °C CUSTOM	S	Cycle can be personalised by user at temperatures 134 °C / 121 °C, process times starting from 4' (134 °C) or 20' (121 °C) with adjustable drying				
VACUUM TEST		TEST	18	18	19	
HELIX/B&D TEST VACUUM		TEST	20	24	28	
+ HELIX / B&D TEST (executed in sequence)		TEST	42	46	51	

\* Drying varies according to machine model and volume  
 Note: times do not take the max. pre-heating time into account (10 min.).  
 Note: times may vary depending on the load and power supply.  
 Note: 120 V model times may undergo increments up to a max. of 20%.

**Sede legale ed amministrativa**  
**Headquarters**  
 Cefla s.c.  
 Via Selice Provinciale, 23/a  
 40026 Imola - Bo (Italy)  
 tel. +39 0542 653111  
 fax +39 0542 653344

**Stabilimento / Plant**  
 Via Bicocca, 14/c  
 40026 Imola - Bo (Italy)  
 tel. +39 0542 653441  
 fax +39 0542 653601



Due to our policy of constant technological upgrading, the technical specifications may be subject to change without prior notice. According to the regulations in force, some products and/or features may have different availability and characteristics in areas outside of the European Union. Please contact your local distributor.

# SOLID INNOVATION

## ANTHOS A PLUS AUTOCLAVES

- A-17 PLUS
- A-22 PLUS
- A-28 PLUS

# A PLUS.

# renew



# Mains water is all it needs

## INCORPORATED FILTRATION IN A STAND-ALONE MACHINE

### Operating principle

Unlike traditional sterilisers, A Plus does not require any external water connection for mains water treatment. Thanks to the demineralisation filter on the main tank, the user can fill the latter with plain tap water, thereby significantly optimising spaces, streamlining processes and achieving considerable savings. A Plus filtration system guarantees unprecedented ease of operation.

### Efficiency and saving

Never before has a steriliser provided such high performance and low usage costs. Since water is demineralised by A Plus filter, the user does not need to source demineralised water: they will only have to fill up the machine tank with tap water. Recipients' storage and deterioration of machine internal components caused by poor water quality will be a thing of the past.



### LCD DISPLAY.

A Plus is a smart and essential working tool that ensures excellent performance also thanks to the colour LCD touch screen and user-friendly interface. Each check is represented by icons that make it easy to identify current machine status.




### Di.V.A.

Di.V.A. stands for Digital Virtual Assistant. It is the first cloud-based control and traceability system for sterilisation devices. Once saved, data will be available for operators by accessing a dedicated web page.



### Remote technical support with Easy Check.

All sterilisers of the A Plus range are equipped with incorporated Wi-Fi and Ethernet port. Connected to the Internet by enabling the Easy Check service, they can receive remote support. Intervention times can be significantly reduced thereby allowing technicians to keep machines constantly efficient.



### 3 volumes, one size.

The A Plus range is available in the 17, 22, and 28-litre versions. Three different capacities allow users to choose the most suitable machine according to their needs. External dimensions, being the same for the three machines, make installation easier. The 17 and 22 litre models have five trays while the 28-litre model has six.



### Traceability software.

MyTrace is the traceability software available for A Plus. By using this programme, each set of sterilised instruments can be associated to the patient through a bar code. This essential software completes the sterilisation process and provides legal protection to dentists.



### Printer.

The A Plus range can be completed with an external printer available as an optional accessory, able to provide reports or bar code labels.